

What is claimed is:

1. A painting device for applying a painted pinstripe to a surface, said device comprising:

a paint applicator including:

a container having an open end and an interior chamber for holding a charge of paint;

a head provided with a slot which communicates with said interior chamber of said container and a striping wheel having an outer annular surface, and said striping wheel rotatably mounted in said slot so that a segment of said outer annular surface protrudes from said slot, and said slot and said striping wheel being arranged so that the outer annular surface enters said head, in communication with said interior chamber of said container, and said striping wheel being structured and disposed to carry the paint on said outer annular surface upon rotation thereof and exposure of said outer annular surface to said charge of paint within said interior chamber; and

an adaptor for attaching said head to said open end of said container, and said adaptor including a distal portion structured and disposed for liquid-tight attachment to said head, and a proximal portion structured and disposed for liquid-tight attachment to said open end of said container so that said slot and a segment of said striping wheel entering said

head through said slot are disposed in liquid communication with said interior chamber and the charge of paint contained therein;

a magnetized flexible guide track having a back surface structured and disposed for mating, releasable attachment to a mounting surface and at least one rail protruding from an opposite front face of said guide track and extending longitudinally therealong, said rail having a rounded exterior surface;

a traveler having at least one roller rotatably supported thereon, said at least one roller including a concave annular recessed surface for congruent, mating engagement with said rounded exterior surface of said rail on said guide track for guiding rolling movement of said traveler along said rail of said guide track;

a connecting arm for adjustably coupling said paint applicator to said traveler, said connecting arm being adjustably attachable to said traveler at a first end portion and said connecting arm being pivotally attached to said paint applicator at an opposite second end portion, and said pivotal attachment of said connecting arm to said paint applicator being structured and disposed to permit pivotal adjustment of said paint applicator throughout a range of selectively adjusted, fixed positions relative to said connecting arm and said traveler, and said connection of said first end portion of said connecting arm to said traveler being structured and disposed to permit selective adjustment of the distance between said striping wheel and said at least one roller of said traveler throughout a range of selectively adjusted fixed positions.